

# INDEPENDENT HEAT

## 120kW



Wall Hung



NOx Class 6



Cascade control




Flueing options



Available in outputs of 40, 60, 80, 100, 120 and 150kW, Independent Heat is designed to ensure all installation requirements can be achieved. There is also an LPG range from 40 to 80kW for off mains installations.

## Features & specification

- 5 year warranty\*
- Robust cast aluminium silicon alloy heat exchanger
- NOx <40mg/kWh (Class 6) for all natural gas models
- High 5:1 turndown
- Up to 99.6% full load efficiency
- Up to 110% part load efficiency
- Exactly the same compact footprint as Evomax, allowing for easy like for like replacement
- Dynamic control menu set up
- Cascade controls option
- Easy servicing; 3 sides removable
- Built in, serviceable flue Non-Return Valve
- Fully compatible with all Evomax 2 accessories



### DIMENSIONS & CLEARANCES

BOILER	DIM A	DIM B
120	360	130


The following minimum clearances must be maintained for operation and servicing:



CLEARANCE BETWEEN MULTIPLE BOILER INSTALLATIONS: 25mm



A



**BOILER ASSEMBLY**  
**INTERNAL VIEW**  
**(40kW MODEL SHOWN)**

### KEY

1. Auto Air Vent
2. Burner Fixings
3. Fan
4. Gas Valve
5. Venturi
6. Flow Thermistor
7. Ignitor Unit
8. Electrode Detection
9. Ignition Electrode
10. Water Pressure Sensor

# INDEPENDENT HEAT 120kW

## TECHNICAL SPECIFICATIONS

### GENERAL

Dry Weight	kg	73
Boiler Dimensions	mm	850 (H) x 500 (W) x 520 (D)
Boiler Clearances	mm	Front: 450 Side: 25 Below: 300
Full Load Efficiency	%	98
Part Load Efficiency	%	109.4
Seasonal Efficiency	%	96.6
SEDBUK 2009	%	N/A
Min/Max Gas pressure	mbar	17.5/20.0

### BURNER PRE MIX

Fuel	(Type G20)	Natural Gas
Fuel Consumption (Nat Gas)	m³/h	13
Flame Protection		Ionisation
Ignition		Spark
Boiler Output (Mean 70°C)	kW	24 - 120
Boiler Output (Mean 40°C)	kW	26 - 124.7
Boiler Input (Gross cv)	kW	136.4
Gas Inlet Size		G¾"
NOx Weighted (gross)	mg/kWh	33.9
NOx Class		Class 6

### HYDRAULICS

Hydraulic Resistance (11°C ΔT)	mbar	N/A
Hydraulic Resistance (20°C ΔT)	mbar	218
Hydraulic Resistance (30°C ΔT)	mbar	80
Nominal Flow Rate (11°C ΔT)	l/min	N/A
Nominal Flow Rate (20°C ΔT)	l/min	86
Nominal Flow Rate (30°C ΔT)	l/min	57.3
Min Flow Rate (30°C ΔT) (MAX MOD)	l/min	58.5
Min Flow Temperature	°C	30
Max Flow Temperature	°C	85
Min Working Pressure	bar	0.3
Max Working Pressure	bar	6
Max Static Head Of Water	metres	61.0
Condensate Connection	mm	25
High Limit Set Point	°C	110 flow, 95 return
Flow & Return Size		G1¼"
Water Content	litres	7.0

### FLUE/AIR INLET

Flue Size	mm	100/150 Concentric or Open Flue
Flue Gas Volume	m³/h	173.33
Flue Gas Temperature 80/60	°C	70
O/F Max Counter Pressure Diff	Pa	473
Balanced Flue Counter Pressure Diff	Pa	0

### ELECTRICAL

Electrical Supply		230V - 50Hz
Current (Max No Pump)	amp	4A
Power Consumption	watt	243
Modulating Input	V/dc	0-10V or OpenTherm
Fuse Rating	amp	4.0
Controls Voltage	V	230V 50Hz volt free control or PELV ≤24V DC
Insulation Class IP		IPX4D

### CONTROL OPERATION

On/Off 0-10V DC	Yes
OpenTherm	Yes
High Limit Protection	Yes
Low Water Protection	Yes
Volt Free Common Alarm	Yes
Boiler Run Indication	Yes

### OPTIONAL EVOMAX 2 KITS FOR INDEPENDENT HEAT

Multi Boiler Frame & Header Kits	Yes
Varican Module Master Kit	Yes
Varican Module Slave Kit	Yes
Extension Module Kit	Yes
OPENTHERM Room Control Kit	Yes
Room Sensor Kit	Yes
Tank Sensor Kit	Yes
Outside Sensor Kit	Yes
Header Flow Tank Immersion Sensor Kit	Yes
Header Flow Tank Strap On Sensor Kit	Yes
Safety Interlock Kit	Yes
0-10V Pump Control Kit	Yes
Condensate Pump	Yes

\*5 year warranty subject to Terms and Conditions. 5 years parts and labour warranty available subject to being commissioned by Ideal Heating. Terms & conditions available at [idealheating.com](http://idealheating.com)

# GET A QUOTE

W: [idealheating.com](http://idealheating.com)

E: [commercial@idealheating.com](mailto:commercial@idealheating.com)

T: 0844 543 6060



Please note that the above information is correct at time of publication. Ideal Heating has a policy of continuous development and therefore reserves the right to alter product specifications or any other details without prior notification.